



INSULATED TUBING & PIPE SUPPORTS

HVAC REFRIGERATION COMPONENTS

CUSH-A-NATOR®



- Standard Temp. Range -50°F to 275°F
- High Temp. Range -65°F to 340°F
- High Intensity Temp. Range -65°F to 400°F
- Perfect for Retrofit / Replacement Applications
- Longer Life Against Vibration Fatigue
- Easy to Replace Without Moving Pipe or Tube

CUSH-A-BLOCK®



- Resistant to Freeze - Thaw Cycles
- Amazing Rooftop Support Configuration Options
- Built-in Channel Guide & Embedded Fasteners
- 100% Recycled Rubber Qualifies - LEED Credits
- Dampens Vibrations
- Eco-Green Reflective Safety Strip Won't Peel

CUSH-A-THERM®



- Service Temp., Continuous: -328°F to +257°F
- Maintains Thermal Barrier Protection
- Prevents Condensation Leaks
- Self-Extinguishing Polyurethane

SNAP-A-SADDLE PRO™



- Click-On Cartridges For:
Strut, Clevis Hangers, Steel Angles,
H-Beam/I-Beam, Floor Adapters
- Permanent Solutions to Insulation Problems

Wesanco-ZSi.com | 800-323-7053

ZSi & Wesanco are part of the Ideal Tridon Group. Learn more at idealtridongroup.com



ALPHA SERIES™



SNAP-A-SADDLE®



CUSH-A-CLAW®



CUSH-A-GRIP



AIRSTRIP®



CUSH-A-CLIP®



SNAP-A-SADDLE PRO MULTI™



CUSH-A-CLICK




LOOP CLAMPS



CUSH-A-STRIP™



GAMMA PADS



METAL FRAMING - Cut Strut and Fittings - Domestic Rolled Channel In-Stock



- Cut Strut Size Range: 6" thru 96" in 6" Increments, Standard Strut Lengths: 10' and 20'
- Solid Single or Combination Strut, Available with Pierced with Holes, Slots, Long Slots, or Knockouts
- Weldless Connections, Strong, Fast, Economical
- 100% Adjustable, 100% Reusable, No Drilling, No Special Tools
- Wide Range of Materials and Finishes including Stainless Steel
- Vast Assortment of Fittings and Accessories to Complete Every Project