

Roundhead Machine Screws



SPECIFYING Brand & Part No.	Size UNC	DISCONTINUED Brands & Part No.	
		VERSABAR	FLORIDA STRUT
WESANCO RHMS25X050	1/4" x 1/2"	25X50RHMS	--
RHMS25X075	1/4" x 3/4"	25X75RHMS	W7470
RHMS25X100	1/4" x 1"	25X1RHMS	W7471
RHMS25X125	1/4" x 1-1/4"	25X125RHMS	W7472
RHMS31X100	5/16" x 1"	31X1RHMS	W7473
RHMS31X125	5/16" x 1-1/4"	31X125RHMS	W7474
RHMS31X150	5/16" x 1-1/2"	31X150RHMS	W7475
RHMS37X100	3/8" x 1"	37X1RHMS	W7476
RHMS37X125	3/8" x 1-1/4"	37X125RHMS	W7477
RHMS37X150	3/8" x 1-1/2"	37X150RHMS	W7478
RHMS37X250	3/8" x 2-1/2"	37X250RHMS	W7479

Standard Finish: Electro-Galvanized (EG)

Finish or Material Order Codes			
Material/Finish	ASTM Designation	Material/Finish Codes	Description
Bar Stock	A 569		Merchant quality hot rolled carbon steel bars.
Hardware	A 563 or A 307		Carbon and alloy steel nuts. Carbon steel externally threaded standard fasteners.
Electroplated	B 633.	EG	Fittings and hardware supplied as "Electro-Galvanized" in accordance with ASTM B 633.
Mill-Galvanized (Pre-Galvanized)	A 653 SS GR33 G90.	PG	Galvanized steel used in the manufacture of channel sections. Uncoated edges resulted from slitting, punching and channel cut off are present.
Hot Dip Galvanized After Fabrication	ASTM A 123, ASTM A153, or ASTM A386.	HG	Channel and fittings which are hot dip galvanized after fabrication.
Special Coatings Yellow Passivate (Trivalent Chromium)	ASTM B63	YC	Fittings and hardware supplied as "Electro-Galvanized", with a "Yellow" Dichromate conversion coat versus the clear conversion coat of the EG finish.
Stainless Steel:	A 240 TYPE 304	S4	Heat resisting chromium and chromium-nickel stainless steel plate, sheet, strip for pressure vessel.
	A 240 TYPE 316	S6	
Aluminum	B 221 TYPE 6063 T6	AL	Aluminum alloy extruded bar, rod, wire, shape and tube.

PROJECT INFORMATION:		APPROVAL STAMP:
Project:		
Date:	Phone:	
Architect / Engineer:		
Contractor:		
Address:		
Notes 1:		