

SUBMITTAL SHEETS



Spring Steel



Conduit and Cable Supports

BR

Bridle Ring



Part No.	Ring Size I.D.	Thread Size
BR1012	3/4"	#10-24
BR1020	1-1/4"	#10-24
BR2520		1/4"-20
BR2520WS		1/4" Wood Screw
BR1032	2"	#10-24
BR2532		1/4"-20
BR2532WS		1/4" Wood Screw

- Supports low voltage communication cable.
- Compatible with many other fasteners for support from purlin, T-grid, drop wire, and beam flanges.
- **Material:** Steel
- **Finish:** Electro-galvanized

Finish or Material Order Codes			
Material/Finish	ASTM Designation	Material/Finish Codes	Description
Carbon Steel	ASTM A1011-00 SS GR 33 or ASTM A1011-00CS Type B	See Finishes Below	Steel
Spring Steel	ASTM A684 Grade 1055	See Finishes Below	Cold rolled Spring Steel sheet
Silva-Guard	--	SG	Silva-Guard coating is a multi-step process that meets the 1000 hour salt spray test per ASTM B117 and DIN 50021. Silva-Guard coating is WEEE, ELV and RoHS compliant. SG Finish is approved for outdoor as well as indoor applications. It is a chrome free duplex coating system that combines an inorganic zinc-rich base coat with an aluminum-rich organic topcoat.
Electroplated	ASTM B 633 SC1 or SC3, Type III	EG	This coating is standard for most products. Electroplating deposits zinc on the surface of the steel by electrolysis from a bath of zinc salts.
Pre-Galvanized	A 653 SS GR33 G90.	PG	Pre-galvanized zinc is produced by continuously rolling steel coils or sheets through molten zinc at the mills.

PROJECT INFORMATION:		APPROVAL STAMP:
Project:		
Date:	Phone:	
Architect / Engineer:		
Contractor:		
Address:		
Notes 1:		

BR